

04-14-00


A

04/13/00

04/13/00

09/548862

04/13/00

UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</small>		Attorney Docket No. 102055-0008P1	
		First Inventor or Application Identifier Paul Andrew Cronk	
		Title ADJUSTABLE REFLECTOR DEVICE	
		Express Mail Label No. EL056798127US	
APPLICATION ELEMENTS See MPEP chapter 600 concerning utility application contents		ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231	
<input checked="" type="checkbox"/> *Fee Transmittal Form (e.g., PTO/SB/17) <small>(Submit an original and a duplicate for fee processing)</small>		6. <input type="checkbox"/> Microfiche Computer Program (Appendix)	
2. <input checked="" type="checkbox"/> Specification [Total Pages 10] <small>(preferred arrangement set forth below)</small>		7. Nucleotide and/or Amino Acid Sequence Sequence Submission <small>((if applicable, all necessary))</small>	
<ul style="list-style-type: none">- Descriptive title of the Invention- Cross References to Related Applications- Statement Regarding Fed sponsored R & D- Reference to Microfiche Appendix- Background of the Invention- Brief Summary of the Invention- Brief Description of the Drawings (if filed)- Detailed Description- Claim(s)- Abstract of the Disclosure		a. <input type="checkbox"/> Computer Readable Copy	
3. <input checked="" type="checkbox"/> Drawing(s) [Total Sheets 4]		b. <input type="checkbox"/> Paper Copy (Identical to computer copy)	
4. Oath or Declaration [Total Pages]		c. <input type="checkbox"/> Statement verifying identity of above copies	
a. <input type="checkbox"/> Newly executed (original copy)		ACCOMPANYING APPLICATION PARTS	
b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) <small>(for continuation/divisional with Box 17 completed)</small> [Note Box 5 below]		8. <input type="checkbox"/> Assignment Papers (cover sheet & document(s))	
DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b)		9. <input type="checkbox"/> Statement (when there is <input type="checkbox"/> Power of Attorney an assignee)	
5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein		10. <input type="checkbox"/> English Translation Document (if applicable)	
		11. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations	
		12. <input type="checkbox"/> Preliminary Amendment	
		13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)	
		14. <input type="checkbox"/> Statement(s) <input type="checkbox"/> Statement filed in prior application, Status still proper and desired ((PTO/SB/09-12))	
		15. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)	
		16. <input type="checkbox"/> Other:	
*NOTE FOR ITEMS 1 & 14: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C. F. R. § 1.27). EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C. F. R. § 1.28).			
17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information below and in a preliminary amendment: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input checked="" type="checkbox"/> Continuation-in-part (CIP) of prior application No.: 8/952,628 Prior application Information: Examiner Tso, L Group/Art Unit: 2875			
18. CORRESPONDENCE ADDRESS			
<input type="checkbox"/> Customer Number or Bar Code Label		or <input checked="" type="checkbox"/> Correspondence address below (Insert Customer No. or Attach bar code label here)	
Name	John F. McKenna		
Address	Cesari and McKenna 30 Rowes Wharf		
City	Boston	State	MA
Zip Code	02110		
Country	U. S. A.	Telephone	(617) 951-2500
		Fax	(617) 951-3927
Name (Print/Type)	John F. McKenna	Registration No. (Attorney/Agent)	20,912
Signature		Date	April 13, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re The Application of:)
Paul Andrew Cronk)
Serial No.: Not yet assigned) Examiner: Not yet assigned
Filed: April 13, 2000)
For: ADJUSTABLE REFLECTOR DE-) Art Unit: Not yet assigned
VICE)
Cesari and McKenna, LLP
30 Rowes Wharf
Boston, MA 02110
April 13, 2000

EXPRESS-MAIL DEPOSIT

“Express Mail” Mailing-Label Number: EL056798127US

The following papers are being deposited with the United States Postal Service
“Express Mail Post Office to Addressee” service pursuant to 37 C.F.R. §1.10:

X Continuation-in-Part Patent Application (10 pages including 11 claims)
X Fee Transmittal Letter X Utility Patent Application Transmittal
Letter
X Formal Drawing (4 sheets) X Check in the amount of \$345.00
X Preliminary Amendment

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re The Application of:)
Paul Andrew Cronk)
Serial No.: Not yet assigned) Examiner: Not yet assigned
Filed: April 13, 2000)
For: ADJUSTABLE REFLECTOR) Art Unit: Not yet assigned
DEVICE)
)
)

Cesari and McKenna, LLP
30 Rowes Wharf
Boston, MA 02110
April 13, 2000

"Express Mail" Mailing-Label Number: EL056798127US

Honorable Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

PRELIMINARY AMENDMENT

In the Specifications:

Page 1, before line 3, insert the following:

Related Application

This application is a continuation-in-part of serial number 08/952,628,
filed March 10, 1998, now patent _____.--

Page 1, line 8, change "industries" to -industries'--;

Page 5, line 6, before "is" insert --there--.

In the Abstract, delete all the identifying numerals and parentheses.

REMARKS


The above amendments address formal matters.

We request consideration on the merits of claims 1 to 11.

Please charge any additional fee occasioned by this paper to our Deposit Account

No. 03-1237.

Respectfully submitted,



John F. McKenna
Reg. No. 20,912
CESARI AND MCKENNA, LLP
30 Rowes Wharf
Boston, MA 02110-2699
(617) 951-2500

UNITED STATES PATENT APPLICATION

of

Paul Andrew Cronk

for

ADJUSTABLE REFLECTOR DEVICE

- 1 -

SHIELDING DEVICE

Background of the Invention

This invention relates to improvements in devices for reflecting light emitted by artificial
5 sources.

Description of the Prior Art

Modern industries requirements for artificial lighting are extensive, varied, and constantly expanding.

10

Many types of reflector devices associated with artificial illumination of industrial spaces are currently known, but these all require that a fixed shape and/or a fixed lamp mounting position within that shape be precisely specified to create optimal light distribution for a particular purpose. For example, a 'chinaman hat' reflector might commonly be used in a situation where a wide, uniform spread of light is required. In this case, the spreading of light is largely dependant on the fixed internal angle of the cone shaped 'chinaman hat' reflector. The uniformity of light emitted is therefore largely dependant on the non-adjustable lamp positioning within that reflector. These known devices have the disadvantage that their rigid, non-adjustable, designs limit their efficient use to a relatively small range of applications.

20

The Applicant's related Australian Serial No. 716550 (and foreign equivalents) relates to a novel reflector having adjustable curvature, which overcomes such disadvantages of the prior art.

25 Horizontally mounted lamps coupled with appropriate reflectors, such as defined in the
aforementioned Patent No. 716550, are popular and fulfil industries requirements in most cases,
however, their efficiency is limited. The closer these fittings can be placed to the 'target area'
the better the overall efficiency and the greater the intensity. However, there comes a point
where the intensity and heat of the light beam directly below the lamp (focal hot spot) limits
30 closer placement. In these conditions, addition of a 'heat shield' (as outlined below) can help

04130

04130

04130

04130

04130

04130

04130

04130

- 4 -

flexing, depicting the transverse alignment of sheet members;

FIG. 6 illustrates the incident and reflected electromagnetic radiation when a double-parabolic reflector is used without a shielding device; and,

FIG. 7 illustrates a similar depiction to that of FIG. 6, but when a shielding device, in
5 accordance with the present invention is used.

Detailed Description of the Preferred Embodiment(s)

Throughout the drawings, like numerals will be utilised to represent similar features, except where expressly otherwise indicated.

10

Also, throughout the specification, the term "a double parabolic" is utilised to describe the shape of a reflector device when it is in its flexed position, and retained against the bias of its normal resilience, as for example, shown in Fig. 3 of the drawings. In considering this definition, it should be appreciated that any size, shape or width of double parabolic or similar
15 shape should be considered to fall within the scope of this definition.

The present invention provides a shielding device, which is substantially V-shaped and perforated, and which is used in association with a reflector device. A preferred arrangement of a reflector device which may be used, is adjustable light reflector device having a resilient
20 reflective skin, flexed to form a double parabolic shape, which is held in place against its resiliency by adjustable retainers located at each end of the skin and an independently adjustable lamp mount which attaches to the skin when it is in the retained position.

Referring to FIG. 1, there is shown a shielding device 17, which is generally V-shaped.
25 which may be attached to a lamp fitting or lamp socket by means of an attachment means 28.

The attachment means 28 is shown embodied as a cylindrical sleeve, which may be secured by a grub screw 19 to the lamp fitting or lamp socket. An arm 29 connects the attachment means 28 to the shielding device 18. The shielding device 17 is provided with perforations 30, which will allow the transmission of some radiant emissions therethrough, whilst other radiant
30 emissions will be reflected by the surface of the shielding device, as will be further detailed

- 5 -

hereinafter. The sizing, spacing, patterning, etc., of the perforations will control the amount of radiation which is transmitted past the device 17, through the perforations 30, and that which is reflected by the device 18, and can thus be predetermined depending upon the amount of radiation required according to the application, the type of reflector used, etc.

5

Referring to Fig. 2, is shown an alternative, but also preferred, embodiment of the invention. In the embodiment of Fig. 2, the reflector may also be described as V-shaped, but it's ends are also pitched, somewhat resembling a 'house-roof' shape. The shielding device 17 of Fig. 2 will disperse light and heat in four directions from the 'hot spot'. That is, the radiation
10 will be reflected left, right, forward and behind the emission source, such as exemplified in Figs. 8(a) to 8(b), which will be described hereinafter. The embodiment of Fig. 2 also shows an alternative embodiment of an attachment means 28, in this case, the attachment means 28 includes a bolt-on-bracket arrangement.

Referring to FIG. 3 it can be seen that a preferred embodiment of adjustable reflector device used in conjunction with the shielding device of this invention includes a two piece resilient skin formed by two members 1 and 2, having a protruding skirt parallel with the longest edge thereof. The sheet members are substantially rectangularly shaped sheet, detachably joined about a spine portion 3 then flexed back against its normal resilience to
20 produce a double parabolic shape, as shown, such that one edge and associated skirt of one sheet member fits neatly inside the corresponding skirt and edge of the other. The sheets are then fixed together and flexed back to achieve a curved shape, such as a double-parabolic shape. The skin may be made of any suitable material such as colour bonded metal, metal, fibreglass, or plastic. The pair of sheet members could be integrally manufactured in a one piece construction
25 - as opposed to being separately formed. These sheets are adjustably secured by a pair of chain 4 and hook 5 retainers (only one retainer shown because of orientation). The retaining means may be a chain, wire or like means, optionally adjustable in length. A pair of threaded bolts 6 and 7 pass down through holes 8 and 9 in the top of the assembled skin and are secured by nuts 10 and 11.

30

[illegible][illegible][illegible][illegible][illegible]

- 7 -

It will be realised that the reflector device according to this invention is not restricted to the specific shape and construction of the resilient skin shown in the example, but may use a skin fashioned from one, two, or more pieces of suitable material of any suitable shape or size so long as the essential feature of being flexed back against a spine or axial crease to create an adjustable double parabolic shape or other similar shape is achieved.

Referring to Fig. 6, a double-parabolic shaped reflector device is shown in cross-section, to illustrate the incident and reflected radiation associated with such a reflector from a light source positioned thereunder. Incident light I is shown being transmitted from the light source. Some of this incident light travels towards the reflector and is reflected as reflected light R, according to the general principle that the Angle of Reflection equals the Angle of Incidence. The double parabolic shaped reflector shown in Fig. 6 is a special shape so far as reflection is concerned, in that it does not reflect any heat or light back towards the light source or bulb, or create any 'left to right' or 'right to left' cross reflection, which is very inefficient.

15

Fig. 7 illustrates a diagram similar to that of Fig. 6, but in which a shielding device 17 in accordance with the present invention is used. In the illustrated arrangement, incident light passing through the shielding device 17 is represented as I_h , whilst light reflected by the shielding device is represented as R_h . Using the double parabolic shaped reflector, as shown in Fig. 7, in conjunction with the heat shield 18, cannot produce any re-reflection of any substantial quantity. It is considered that re-reflection would still be minimal in the event that a non-parabolic reflector is used.

It will be appreciated by persons skilled in the art that variations and modifications may be made to the shielding device of the present invention, whilst still achieving the functional advantages of the described embodiments. As such, variations to the shape, the nature and extent of the perforations, the means of attachment, etc., should all be considered to fall within the scope of the invention as hereinbefore described and as hereafter claimed.

- 8 -

THE CLAIMS

1. A shielding device adapted to be disposed about at least part of a lighting means, said device being substantially V-shaped and perforated.
- 5 2. A shielding device as claimed in claim 1, wherein said device is adapted to be attached to a lamp socket or lamp bracket of said lighting means.
3. A shielding device as claimed in claim 1, wherein said device is positioned on the opposed side of said lighting means relative to a reflector device associated with said lighting
10 means.
4. A shielding device as claimed in claim 1, wherein said shielding device acts to at least partly deflect heat and/or light emitted from said lighting device, to thereby control the amount and lateral spread of radiation emitted directly from said lighting means.
15
5. A shielding device as claimed in claim 4, wherein the nature and/or extent of perforation of said shielding device is predetermined to control the amount of radiation deflected by said shielding device.
- 20 6. A shielding device as claimed in claim 1, wherein said perforations are embodied in a patterned manner, such as in rows or the like.
7. A shielding device as claimed in claim 4, wherein radiation deflected from said device is transmitted away from said reflector device in a broad pattern largely independent of the
25 shape of said device.
8. A shielding device as claimed in claim 4, wherein said reflector device has adjustable curvature.

30

— — — — —

S A M S O N I C S E T A B L E T T E S - P a g e 1 1

- 10

- 10 -

ABSTRACT

An adjustable reflector device is disclosed. The device consists of an adjustable double parabolic reflective skin (1,2) with an adjustable lamp mount (12), incorporating a V- shaped
5 perforated heat shield (17), attached. The two part reflective skin (1,2) forms a double parabolic shape when flexed back against a reinforced spine(3). This flexible shape is secured by lengthwise adjustable chain retainers (4) attached a both ends of the skin (1,2). The lamp mount (12) slides onto a pair of threaded bolts (6,7) secured to the skin and adjustment is achieved by tightening or loosening the appropriate nuts (15,16). The heat shield (17) slides onto the lamp
10 fitting (18) and is positioned appropriately to deflect incident heat and light. This device can be used to provide variable conditions of artificial illumination.

002740-2383450




FIG. 1 19




FIG. 2

